



Web

Results 1 - 10 of about 118 for cluster queue lock message wireless transaction server noncluster OR non-cluster. (0.47 seconds)



Show options...

Did you mean: cluster queue lock message wireless transaction server **non cluster** OR non-cluster

1. Sun Java Enterprise System Glossary

The CMM ensures that **non-cluster** members cannot corrupt data and A quick reconfiguration of the Distributed **Lock Manager** is performed to Interpreted as a packaged enterprise application, a **transaction** system, or a user application.

Message Queue message server (n.) Software that provides delivery ...

docs.sun.com/source/816-6873/index.html - Cached - Similar

2. [PDF] Oracle Application **Server** Integration Installation Guide

File Format: PDF/Adobe Acrobat - View as HTML

Step 6: If Installing on a Cold Failover **Cluster (CFC)** Middle Tier Optimizing **Transaction** Timeout for Oracle BPEL **Server** and short **message** service (SMS) channels, then the **wireless** service settings must The name of the **queue** manager that provides access to the **queues** ...

download.oracle.com/docs/cd/B28095_05/pc.1012/b25760.pdf - Similar

3. Database Error Messages

1-6 Oracle9i Database Error Messages Part II Oracle Database Server Messages

instance Cause: **Cluster** database command issued for **non cluster** database

ORA-01591 lock held by in-doubt distributed transaction string Cause: An Action:

If there is no **message queue**, restart the SQL*Net IPA servers ...

www.scribd.com/doc/19282837/Database-Error-Messages - Cached - Similar

4. Mike Kruckenberg: April 2004 Archives

Someone on MySQL Team: When the cache finds a result it will **lock** that result, not everything else. but the standards docs always pronounce it Ess **Queue** Ell.

The MySQL server uses the NDB API interface to get data from the cluster. ...

wanting to have **non-cluster** environments with data from the **cluster**. ...

mike.kruckenberg.com/archives/2004/04/ - [Cached](#) - [Similar](#)

5. [JBoss Application Server 5.0.0](#)

JBoss Transactions is the default **transaction** manager for JBoss 5. ... Jboss Mitigates risks and helps customers avoid vendor **lock in**. JBoss Messaging provides a **message** counter for each **queue**. The simplest way to start a JBoss **server cluster** is to start several JBoss instances on the same local ...

www.jboss.org/file-access/default/.../Server.../index.html - [Cached](#) - [Similar](#)

6. [\[PDF\] Ensuring High Availability with Microsoft Exchange Server](#)

File Format: PDF/Adobe Acrobat - [View as HTML](#)

You need to **lock** down your Exchange **cluster** to prevent the spread of W32.Blaster. Worm, the that occurs to Exchange databases and **transaction** logs. ... While you're at it, make sure that your **server** and **message** monitors are functional—they ... For example, suppose a mail connector **queue** fills **Server A's** hard ...

www.doubletake.com/_.../white-paper-ensuring-high-availability-with-ms-exchange-server.pdf - [Similar](#)

7. [\[PDF\] Pramati Server](#)

File Format: PDF/Adobe Acrobat

Information related to **Message Server Queues** and Topics are stored here. distributes the Web requests even across **non-cluster server** instances and WAP: Notification of an alert over the **Wireless** Application Protocol, to mobile phones or The **lock** is released only when the **transaction** completes. ...

www.pramati.com/docstore/1500009/psv50techref.pdf - [Similar](#)

8. [\[PDF\] Server™ and WebLogic Express o](#)

File Format: PDF/Adobe Acrobat

Jump to [Starting and Killing All WebLogic Servers in a Domain or Cluster ...](#): To view the **messages** as they are being printed to the file, open a command for **wireless** applications Note: For **non-cluster** servers, JMS **queue**—the **transaction** will still **Lock** WebLogic. **Server. LOCK** ...

edocs.bea.com/wls/docs70/pdf/adminguide.pdf - [Similar](#)

by BEA WebLogic - [Related articles](#) - [All 49 versions](#)

9. [\[PDF\] IBM E server pSeries Sizing and Capacity Planning](#)

File Format: PDF/Adobe Acrobat

and **transaction** size is always a serious problem on UNIX-based systems. This is **server** handles all aspects of security and **lock** management. **Non-cluster db server** (for example, UDB ESE). – **Cluster db server** (for example, This flag reports **message queue** and shared memory segment information. ...

www.redbooks.ibm.com/redbooks/pdfs/sg247071.pdf - [Similar](#)

by IBMES Sizing

10. [2.6.23-rc1 short-form changelog \[LWN.net\]](#)

[XFS] Lazy Superblock Counters [XFS] Fix the **transaction** flags to make lazy


linville/**wireless**-2.6 into upstream kernel/auditfilter: kill bogus for SRQ IB/ehca: add

Shared Receive **Queue** support IB/ehca: **Lock** renaming, and nfsd4 gfs2: stop

giving out **non-cluster**-coherent leases Marc Pignat (1): mmc: ...

lwn.net/Articles/242483/ - [Cached](#) - [Similar](#)

Did you mean to search for: [cluster queue lock message wireless transaction server](#) ***non cluster*** OR [non-cluster](#)



[Search within results](#) - [Language Tools](#) - [Search Help](#) - [Dissatisfied? Help us improve](#) - [Try Google Experimental](#)

[Google Home](#) - [Advertising Programs](#) - [Business Solutions](#) - [Privacy](#) - [About Google](#)